

0 611 924 0F0 – GBH 185-LI

Material number	0 611 924 0F0
EAN	4059952661360
2 x battery GBA 18V 4.0Ah 1 607 A35 0M0	✓
Quick charger GAL 18V-40 Professional 2 607 226 537	✓



Technical data

Noise/vibration information

Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 94 dB(A); Sound power level 102 dB(A). Uncertainty K= 3 dB.
Tool dimensions (width)	102 mm
Tool dimensions (length)	296 mm
Tool dimensions (height)	208 mm
Battery voltage	18.0 V
Impact energy (according to EPTA 05/2016)	1.9 J
Impact rate at rated speed	0 – 4,675 bpm
Rated speed	0 – 1,050 rpm
Weight excl. battery	2.3 kg
Tool holder	SDS plus
Drilling dia. in concrete with hammer drill bits	4 – 22 mm
Opt. app. range in concrete with hammer drill bits	4 – 12 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	20 mm
Product category subdivision	Cordless Rotary Hammer with SDS plus
BITURBO	No



Sales information

Positioning

- Next-level work with efficiency, safety and control

User benefit

- More holes per charge and continuous power output thanks to motor with constant speed
- Better drilling experience due to Vibration Control, designed to absorb pulsation
- Enhanced safety against accidental jams thanks to KickBack Control
- Dust-free work condition with Auto Power GDE 12 extractor attachment

